



徐工徐工 助您成功
XCMG SOLID TO SUCCEED



HANVAN 漢風 XG1

8 × 4 左驾自卸车XGA3311D2WE

HANVAN XG1 8 × 4 LHD DUMP TRUCK

A detailed side-view technical drawing of a truck. The drawing includes dimension lines and labels for various parts: L1 (front overhang), L2 (first and second wheel base), L3 (second and third wheel base), L4 (third and fourth wheel base), L5 (rear overhang), L6 (container length), L (maximum length), H1 (cab height), H2 (height of container above ground), H3 (container height), H (maximum height), Ba (wheel tread), Bb (overall width), and Bc (maximum width).

A detailed front-view technical drawing of a truck. The drawing includes dimension lines and labels for various parts: Bb (overall width) and Bc (maximum width).

外形尺寸/Appearance size	
L1 前悬/Front overhang	1500mm
L2 第一、二轴轴距/First and second wheel base	1950mm
L3 第二、三轴轴距/Second and third wheel base	3750mm
L4 第三、四轴轴距/Third and fourth wheel base	1450mm
L5 后悬/Rear overhang	1950mm
L6 货箱长度/Container length	7800mm
L 最大长度/Max length	10600mm
H1 驾驶室高度/Cab height	3100mm
H2 货箱离地高度/ Height of container above ground	3160mm
H3 货箱高度/Container height	1500mm
H 最大高度/Max height	3560mm
Ba 轮距/Wheel tread	2013mm
Bb 整车宽度/Overall width	2550mm
Bc 最大宽度/Max width	3150mm

主要参数 / Main Specifications

项目 Items		参数 Parameters	
性能参数/PERFORMANCE PARAMETERS			
驱动形式/Drive Type	8×4		
整备质量/Kerb Mass	21700kg		
最大允许总质量/GVW	70000kg		
最高车速/Max. Speed	77km/h		
最小转弯直径/Min. Turning Diameter	24.4m		
最大爬坡度/Grade Ability	≥ 30%		
油箱容积/Fuel Tank	400L		
尺寸参数/DIMENSIONS			
外形尺寸/Dimension (mm)	10600×2550×3560		
轴距/Wheelbase (mm)	1950+3750+1450		
最小离地间隙/Min. Clearance (mm)	306		
接近角/Approach Angle	28°		
离去角/Departure Angle	42°		
前悬/Front Overhang(mm)	1500		
后悬/Rear Overhang(mm)	1950		
货厢尺寸/Cargo size (mm)	7800×2300×1500		
驾驶室/CABIN			
型号/Model	XG1 H		
左右驾/Left/Right Driving	LHD		
空调/AC	Standard		
乘员人数/Person Allowed in	2		
发动机/ENGINE			
型号/Model	SC10E400Q3B		
排放等级/Emission Standard	EUR II		
总排量/Displacement	10.4L		
额定功率/Output Power	294/1900 kw		
最大扭矩/Max Torque Speed	1650/1400 N·m		

项目 Items			参数 Parameters	
离合器/CLUTCH				
型号/Model		Φ 430拉式膜片弹簧离合器 / Φ 430 Pull type diaphragm spring clutch		
操纵方式/Manipulating		液压操纵气助力/Hydraulic manual		
变速箱/TRANSMISSION				
型号/Model		10JSD180T		
取力器/PTO		QH50		
前进档速比/Forward Ratio		14.98~1.00		
倒档速比/Reverse Ratio		15.113/3.377		
车桥/AXLE				
前桥型号/Front Axle Model		7.5T		
后桥型号/Rear Axle Model		16T		
主减速器速比/Main Reducer Ratio		5.92		
轮胎/TIRE				
轮辋/Rim		8.5V-20	9.00×22.5	
轮胎/Tire		12.00R20	315/80R22.5	
车架/FRAME				
主纵梁截面/HxW-t(mm)		320×90×8		
衬梁截面/Auxiliary beam(mm)		304×82×8		
车架总成宽度/Frame Width(mm)		865		
悬架/SUSPENSION				
前/Front	型式/Type	纵置多片簧/Multi-spring		
	板簧片数/Leaf springs	10		
后/Rear	型式/Type	纵置多片簧/Multi-spring		
	板簧片数/Leaf springs	14		
制动/BRAKE				
类型/Type		鼓式/Drum type		
缓速器/Retarder		/		