XCMG | SOLID TO SUCCEED

CE

SCISSOR LIFT
XG0608HA

Standard configuration

Work Area
- Withdrawable Platform Extension With Position Lock
- Lanyard Attach Points
- Self-Locking Half-Height Swing Gate And Folding Guardrail

Drive
- Front-Wheel Drive

Performance
- Travel Driven By Hydraulic Motor
- Full Proportion Travel And Lift Control
- 25 % Gradeability

Power
- DC Maintenance-Free Battery

Applicability
- Lubrication-Free Bearing
- Swing-Out Component Tray
- Brake Release For Towing

Safe
- Emergency Stop Devices On Platform And Ground Controls
- Anti-Slipping Metal Platform
- Load Sensing Alarm System
- Descent Alarm
- 3-Second Descent Delay
- Multi-Axis Tilt Sensor
- Multi-Disc Brake
- Boom Maintenance Lock
- Auto Brake System
- Pothole Protection Device
- Fault Diagnosis System
- Electric Horn
- Automatic Speed Reduction At Height
- Charging Protection System

Other Features
- Removable Platform Control
- Intelligent Charger
- Hourmeter
- Side Fork Pockets
- Flashing Indicator Light
- User-Friendly Control System
- Platform Control With Battery Level Display
- Manual Platform Descent Valve
- Tilt Sensor And Audio Alarm



Working height
6.0/6.0 meters

Lift capacity
200Kg

Electric
power

Optional configuration

- Platform Searchlight
- Platform External Power Supply
- Air Line
- Platform Fire Extinguisher
- Platform Foot Pedal

XCMG FIRE-FIGHTING SAFETY EQUIPMENT CO., LTD

No.17 Zhujiang East Road, Hi-Tech Development Zone, Xuzhou, Jiangsu, China
mewp@xcmg.com


XG0608HA


XCMG SOLID TO SUCCEED

Scissor Lift-Electric


Item	Metric
Dimension	
Max. Working Height (Indoor/Outdoor)	6.0m/6.0m
Max. Platform Height (Indoor/Outdoor)	4.0m/4.0m
Min. Platform Height	0.96m
Max. Platform Drive Height	4.0m
Overall Length (Stowed)	1568（1480）mm
Overall Width	810mm
Overall Height (Platform Folded)	2076(1714)mm
Platform Length	1372mm
Platform Width	702mm
Platform Extension Length	600mm
Wheelbase	1130mm
Min. Ground Clearance (Pothole Protection Deployed/Undeployed)	33mm/61mm
Tire Size	φ280mm×76mm
Performance	
Rated Load	200kg
Load On Platform Extension	115kg
Max. Platform Occupancy (Indoor/Outdoor)	1/1
Max. Driving Speed (Stowed)	3km/h
Max. Driving Speed (Raised)	0.5km/h
Max. Gradeability	25%
Min. Turning Radius (Inside)	0.45m
Min. Turning Radius (Outside)	1.6m
Platform Raising Time	19-29s
Platform Lowering Time	19-29s
Max. Working Slope (Side To Side/Front And Rear)	1.5°/3°
Tire Ground Pressure	7.49kg/cm^2
Driving Wheels	2
Braking Wheels	2
Steering Wheels	2
Power Source	**Maintenance-free lead-acid batteries**
Battery Voltage	24 V
Battery Capacity (3HR)	120Ah
Battery Charger	24/15V/A
Lifting Motor	2.5/24 kW/V
Hydraulic Oil Capacity	
Hydraulic Tank Capacity	4L
Weight	
Machine Weight	990kg

Trans





Platform Extd



The print does not belong to the contract，nor a part of the commercial contract.We reserve the right to revise the product model，parameters，configuration based on the continuous improvment requirements of the product，without prior notice.Pictures are for reference only，and the specific product shall depend on the real product.The final interpretation rights belong to XCMG.