



SOLID
TO SUCCEED

TELESCOPIC BOOM LIFT XGS58ACK-LI

Standard Configuration

Work Area

- 2.4 m × 0.9 m Work Platform
- Tri-Entry Work Platform
- 460 Kg Platform Capacity
- 160° Platform Rotation

Power

- 12V DC Auxiliary Power

Drive

- 4-Wheel Drive
- Foam-Filled Tire

Safe

- Descent And Motion Alarm
- Tilt Alarm
- Horn
- Overload And Overrange Limit Detection
- Chassis Tilt Protection
- Jib Centering And Swing Detection
- Limit Position Deceleration
- Joystick Self Locking
- Work Platform Tilt Protection
- Wire Rope Slack Detection
- Emergency Stop Devices On Platform And Chassis
- Emergency Power Unit
- 4-Wheel Braking System
- High Pressure Interlock
- Insulation Monitoring

Other Features

- Automatic Leveling System
- Proportional Joystick Control
- Drive Enable
- Hourmeter
- Lockable Engine Hood
- 360° Continuous Turntable Rotation
- Telematics Front-End Interface
- Anti-Entrapment System
- Platform Power
- Tool Tray



Working height
58.8 meters



Lift capacity
300kg/460kg



Electric
power



Options

- Mechanical Anti-Entrapment Device
- Handrail
- Fall Arrest Assembly
- Air Line
- Platform Half-Mesh
- Platform Anti-Squeeze Auxiliary Rail
- Working Light Assembly
- Platform Height Limitation Anti-Collision Device
- Rubber Buffer Protection Device
- Anemometer

XCMG FIRE-FIGHTING SAFETY EQUIPMENT CO., LTD

No.17 Zhujiang East Road, Hi-Tech Development Zone, Xuzhou, Jiangsu, China
mewp@xcmg.com

XGS58ACK-LI



SOLID
TO SUCCEED


Telescopic Boom Lift-Electric

Item	Metric	
Dimension		
Overall Dimension - Stowed	Length	19990mm
	Width	2490mm
	Height	3070mm
Overall Dimension - Transported	Length	15120mm
	Width	2490mm
	Height	3070mm
Platform Dimensions	Length	2400mm
	Width	900mm
	Height	1150mm
Wheelbase (Axle Extended/Retracted)	4590/5220 mm	
Overall Machine Width (Axle Extended/Retracted)	5030mm/2490 mm	
Jib Length (Fully Retracted/Extended)	4647mm/6647mm	
Min. Ground Clearance	430mm	



Performance	
Max. Working Height	58.8m
Max. Platform Height	56.8m
Max. Outreach	25.6m
Max. Lift Capacity	300kg/460kg
Max. Platform Occupancy	2/3
Max. Chassis Allowable Angle	X-5°/ Y-5°
Boom Elevation Range	0° ~ 80°
Fly Boom Luffing Range	-45° ~ 75°
Turntable Rotation	360°
Platform Rotation	160°
Machine Weight	28800kg
Driving Speed (Stowed)	4.5 km/h
Driving Speed (Raised Or Extended)	0.3~0.5 km/h
Min. Turning Radius-Axle Retracted (Inside/Outside)	14000mm/17200mm(2) 7600mm/9500mm(4)
Min. Turning Radius-Axle Extended (Inside/Outside)	3000mm/9300mm(2) 2800mm/6600mm(4)
Turntable Tailswing	2.18m
Max. Gradeability (Counterweight Uphill)	40% (22°)

Power source	
Control	12 V DC proportional control
Main Power Unit	50kW/360V AC
Auxiliary Power Unit	12V/2kW
Emergency Battery Specifications	12V/2×220Ah
Main Power Source - Battery	360V/280Ah
Charger Specifications	32A/304-456V
Hydraulic Tank Capacity (Effective Volume)	250L



Tire	
Tire Size	φ1180mm×445mm
Ply Rating Of Tire	28
Tire Ground Pressure	11kg/cm ²
Driving Wheels	4
Braking Wheels	4
Steering Wheels	4



Stowed



Trans



The print does not belong to the contract, nor a part of the commercial contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product. The final interpretation rights belong to XCMG.