



SOLID
TO SUCCEED

ARTICULATED BOOM LIFT XGA20ACK-LI

Standard configuration

Work Area

- Tri-Entry Platform

Drive

- 4-Wheel Drive
- Axle Oscillation

Safe

- Descent And Motion Alarm
- Tilt Alarm
- Horn
- Overload Alarm
- Motor Overload Protection
- Emergency Stop Devices On Platform And Chassis
- Emergency Power Unit
- 4-Wheel Braking System

Other Features

- Automatic Leveling System
- Proportional Joystick Control
- Drive Enable
- Telematics Front-End Interface
- Boom Gravity Descent System
- Double-Load Amplitude Control
- Hostile Environment Package
- Thumb Rocker Steering
- Anti-Entrapment System



Working height
20.6 meters



Lift capacity
256/350Kg



Electric
power



Optional configuration

- Solid Gray Tires (φ835mm×295mm)
- Platform Power
- Tool Tray
- Air Line
- Mechanical Anti-Entrapment Device
- Platform Height Limitation Anti-Collision Device
- Platform Half-Mesh
- Working Light Assembly
- Fall Arrest Assembly
- Platform Anti-Squeeze Auxiliary Rail
- Aircraft Protection Device
- Rubber Buffer Protection Device

XCMG FIRE-FIGHTING SAFETY EQUIPMENT CO., LTD

No.17 Zhujiang East Road, Hi-Tech Development Zone, Xuzhou, Jiangsu, China
mewp@xcmg.com

XGA20ACK-LI



SOLID
TO SUCCEED


Articulated Boom Lift-Electric

Item	Metric	
Dimensions		
Overall Dimension - Stowed	Length	8490mm
	Width	2490mm
	Height	2380mm
Overall Dimension - Transported	Length	6300mm
	Width	2490mm
	Height	3000mm
Platform Dimensions	Length	1830mm
	Width	760mm
	Height	1150mm
Wheelbase		2500mm
Jib Length		1850mm
Min. Ground Clearance		300mm



Performance	
Max. Working Height	20.6m
Max. Platform Height	18.6m
Max. Outreach	11.98m
Max. Up And Over Clearance	7.85m
Max. Lift Capacity	256/350kg
Max. Platform Occupancy	2/3
Max. Chassis Allowable Angle	X-3°/ Y-3°
1St Boom Luffing Range	0°~72°
2Nd Boom Luffing Range	0°~73°
Fly Boom Luffing Range	-65°~70°
Turntable Rotation	360°
Platform Rotation	160°
Machine Weight	9100kg
Driving Speed (Stowed)	4.8km/h
Driving Speed (Raised Or Extended)	0.6km/h
Min. Turning Radius (Inside/Outside)	2800mm/5000mm
Turntable Tailswing (Stowed)	560mm
Max. Gradeability (Counterweight Downhill)	45% (24°)

Power Source	
Control	12V DC proportional control
Main Power Unit	12kw/31V (AC)
Auxiliary Power Unit	1.9kw/12 V (DC)
Traveling Motor	3.3kw/32 V (AC)
Emergency Power Supply	12V/120Ah
Main Power Source - Battery	51.2V/460Ah (Li)
Main Power Source - Charger	48V/60A
Hydraulic Tank Capacity (Effective Volume)	82L



Tire	
Tire Size	φ835mm×295mm
Tire Ground Pressure	7.19kg/cm ²
Driving Wheels	4
Braking Wheels	4
Steering Wheels	2



Stowed



Trans



The print does not belong to the contract, nor a part of the commercial contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product. The final interpretation rights belong to XCMG.