



SOLID
TO SUCCEED



TELESCOPIC BOOM LIFT XGS40ACK

Standard configuration

Work Area

- Tri-Entry Work Platform

Drive

- 4-Wheel Steer
- X-Swing Axle

Safe

- Descent And Motion Alarm
- Tilt Alarm
- Emergency Stop Devices On Platform And Chassis
- Work Platform Tilt Protection
- Emergency Power Unit
- 4-Wheel Braking System
- Horn
- Overload Alarm

Other Features

- Platform Power
- Tool Tray
- Automatic Leveling System
- Proportional Joystick Control
- Drive Enable
- Anti-Entrapment System
- Thumb Rocker Steering
- Telematics Front-End Interface
- Hostile Environment Package



Working height
40.2 meters



Lift capacity
300/460kg



Electric
power



Optional configuration

- Mechanical Anti-Entrapment Device
- Working Light Assembly
- Platform Half-Mesh
- Air Line
- Fall Arrest Assembly
- Platform Anti-Squeeze Auxiliary Rail
- Aircraft Protection Device
- Platform Height Limitation Anti-Collision Device
- Rubber Buffer Protection Device
- Anemometer
- Foam-Filled Tires (Φ1210mm×445mm)

XCMG FIRE-FIGHTING SAFETY EQUIPMENT CO., LTD

No.17 Zhujiang East Road, Hi-Tech Development Zone, Xuzhou, Jiangsu, China
mewp@xcmg.com


XGS40ACK





SOLID
TO SUCCEED

Telescopic Boom Lift-Electric



Item		Metric
Dimension		
Overall Dimension - Stowed	Length	14990mm
	Width	2400mm
	Height	2810mm
Overall Dimension - Transported	Length	11800mm
	Width	2300mm
	Height	2810mm
Platform Dimensions	Length	2400mm
	Width	900mm
	Height	1150mm
Wheelbase (Axle Retracted/Axle Extended)		4257mm/4000mm
Overall Width (Axle Retracted/Axle Extended)		2400mm/4018mm
Jib Length		2440mm
Min. Ground Clearance		340mm
Performance		
Max. Working Height		40.2m
Max. Platform Height		38.2m
Max. Outreach		22.4m
Max. Lift Capacity		300kg/460kg
Max. Platform Occupancy		2/3
Max. Chassis Allowable Angle		X-5°/ Y-5°
Telescopic Boom Luffing Range		-1.5°~ 75°
Fly Boom Luffing Range		-60°~70°
Turntable Rotation		360°
Platform Rotation		160°
Machine Weight		21000kg
Driving Speed (Stowed)		5km/h
Driving Speed (Raised Or Extended)		0.5km/h
Min. Turning Radius-Axle Retracted (Inside/Outside)		15800mm/18600mm(2)
		7900mm/10200mm(4)
Min. Turning Radius-Axle Extended (Inside/Outside)		3700mm/8800mm(2)
		2400mm/6000mm(4)
Turntable Tailswing		1615mm
Max. Gradeability (Counterweight Uphill)		40%(22°)
Power source		
Control		12 V DC proportional control
Main Power Unit		25.4kW/50V(AC)
Auxiliary Power Unit		1.9kW/12V(DC)
Traveling Motor		5.2kW/52V AC
Emergency Power Supply		12V/120Ah
Main Power Source - Battery		80.5V/604Ah
Main Power Source - Charger		80V/80A
Hydraulic Tank Capacity (Effective Volume)		210L
Tire		
Tire Size		φ1210mm×445mm
Tire Ground Pressure		11kg/cm ²
Driving Wheels		4
Braking Wheels		4
Steering Wheels		4



Stowed



Trans



The print does not belong to the contract, nor a part of the commercial contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product. The final interpretation rights belong to XCMG.