



SOLID
TO SUCCEED



ROUGH TERRAIN SCISSOR LIFT XG1523ERT

Standard configuration

Work Area

- Foldable Guardrail
- Self-Closing Gate
- Bidirectional Platform Extension
- Anti-Slipping Metal Platform
- Lanyard Attach Points

Drive

- 4-Wheel Drive
- Front-Wheel Steering
- 40 % Gradeability

Performance

- Full Proportion Travel And Lift Control
- Axle Oscillation System

Power

- Flooded Lead-Acid Battery

Applicability

- Lubrication-Free Bearing

Safe

- Emergency Stop Button
- Movement Alarm
- Flashing Indicator Light
- Boom Maintenance Lock
- Automatic Drive Restriction At Height
- Tilt Protection System
- Charging Protection System
- Auto Brake System
- Fault Diagnosis System
- Emergency Descent System
- Outrigger Leveling System
- Wheel Hub Drive Motor State Monitoring And Overtemperature Stall Protection System
- Load Sensing Alarm System

Other Features

- Standard Forklift Pockets For Transport
- Tie Down And Lifting Points
- Electric Horn
- Battery Level Display
- Hourmeter
- User-Friendly Control System



Working height
15 meters



Lift capacity
700Kg



Electric
power



Optional configuration

- Low-Speed Drive At Height
- Chassis Protective Fence
- Non-Marking Rubber Tire
- Platform External Power Supply

XCMG FIRE-FIGHTING SAFETY EQUIPMENT CO., LTD

No.17 Zhujiang East Road, Hi-Tech Development Zone, Xuzhou, Jiangsu, China
mewp@xcmg.com

XG1523ERT





SOLID
TO SUCCEED


Rough Terrain Scissor Lift-Electric

Item	Metric
Dimension	
Max. Working Height	15m
Max. Platform Height	13m
Min. Platform Height	1.8m
Maximum Drive Height	3m(Standard) 13m(optional)
Overall Length (Without Ladder/Outriggers)	4860mm
Overall Width	2286mm
Overall Height (Platform Folded)	2950(2290)mm
Platform Length	3980mm
Platform Width	1830mm
Platform Extension Length	1450mm/1140mm
Outrigger Span (Side To Side/ Front And Rear)	1995mm/4280mm
Wheelbase	2850mm
Min. Ground Clearance	253mm
Tire Size	φ835mm×290mm
Performance	
Rated Load	700kg
Load On Platform Extension	230kg
Max. Platform Occupancy (Indoor/Outdoor)	7/7
Max. Driving Speed (Stowed)	5.1km/h
Max. Driving Speed (Raised)	0km/h(Standard) 1.1km/h(optional)
Max. Gradeability	40%
Min. Turning Radius (Inside)	2.5m
Min. Turning Radius (Outside)	5.6m
Platform Raising Time	65s
Platform Lowering Time	45s
Max. Working Slope (Side to Side/Front and Rear)	2°/3°
Tire Ground Pressure	13.3kg/cm ²
Driving Wheels	4
Braking Wheels	4
Steering Wheels	2
Power Source	
Flooded Lead-Acid Battery	
Battery Voltage	48V
Battery Capacity (5HR)	480Ah
Battery Charger	48/35V/A
Traveling Motor	3.3/32kW/V
Lifting Motor	12/31kW/V
Hydraulic Oil Capacity	
Hydraulic Tank Capacity	100L
Weight	
Machine Weight	7640kg

Trans



Platform Extd



The print does not belong to the contract, nor a part of the commercial contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product. The final interpretation rights belong to XCMG.